Bohnenkamp Moving Professionals

17.11.2024

TYRES

Product group	Tyres	
Item number	15712497	
Valid tyre size	16.5 / 85 - 24	
LI / SI / PR	151 A8 / 163 A8, 12 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AS 504	



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Bohnenkamp Moving Professionals

Technical Informations

Item number	15712497
EAN	8903094019090
Valid tyre size	16.5 / 85 - 24
LI / SI / PR	151 A8 / 163 A8, 12 PR
TL/TT	ТL
Brand	ВКТ
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	79,19
Recommended rim size	W13
Permitted rim size	W14L, W15L
Maximum air pressure [bar].	2,80
Section width (mm)	415
Outer diameter of tyre [mm].	1325
Stat. radius (SLR) [mm]	591
Rolling circumference [mm].	3837
Tread depth (mm)	40,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40	Drive Wheel	2,80	LLV
163 A8	4875	40	Free Rolling	2,80	LLV

17.11.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.