

TYRES

Product group	Tyres
Item number	15712498
Valid tyre size	16.5 / 85 - 24
LI / SI / PR	155 A8 / 168 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15712498
EAN	8903094019113
Valid tyre size	16.5 / 85 - 24
LI / SI / PR	155 A8 / 168 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	83,76
Recommended rim size	W13
Permitted rim size	W14L, W15L
Maximum air pressure [bar].	3,80
Section width (mm)	415
Outer diameter of tyre [mm].	1325
Stat. radius (SLR) [mm]	591
Rolling circumference [mm].	3837
Tread depth (mm)	40,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40	Drive Wheel	3,80	LLV
168 A8	5600	40	Free Rolling	3,80	LLV