

TYRES

Product group	Tyres
Item number	15712499
Valid tyre size	500 / 55 - 20
LI / SI / PR	138 A8 / 150 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	15712499
EAN	8903094039234
Valid tyre size	500 / 55 - 20
LI / SI / PR	138 A8 / 150 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	63,52
Recommended rim size	16.00
Maximum air pressure [bar].	2,30
Section width (mm)	508
Outer diameter of tyre [mm].	1058
Stat. radius (SLR) [mm]	458
Rolling circumference [mm].	3153
Tread depth (mm)	19,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40	Drive Wheel	2,30	
150 A8	3350	40	Free Rolling	2,30	