

TYRES

Product group	Tyres
Item number	15712500
Valid tyre size	400 / 55 - 22.5
LI / SI / PR	138 A8 / 150 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Flotation tyre for high payloads with low inflation pressure
- Minimal soil compaction
- Suitable for road and field use

Technical Informations

Item number	15712500
EAN	8903094006243
Valid tyre size	400 / 55 - 22.5
LI / SI / PR	138 A8 / 150 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	50,51
Recommended rim size	AG11.75
Permitted rim size	12.25, 13.00, AG13.00
Maximum air pressure [bar].	3,50
Section width (mm)	405
Outer diameter of tyre [mm].	1020
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	3084
Tread depth (mm)	19,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40	Drive Wheel	3,50	
150 A8	3350	40	Free Rolling	3,50	