

TYRES

Product group	Tyres
Item number	15712505
Valid tyre size	400 / 60 - 22.5
LI / SI / PR	148 A8 / 160 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	15712505
EAN	8903094006328
Valid tyre size	400 / 60 - 22.5
Alternative size 1	385/65-22.5
LI / SI / PR	148 A8 / 160 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,69
Recommended rim size	AG11.75
Maximum air pressure [bar].	4,30
Section width (mm)	400
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3233
Tread depth (mm)	22,0
Number of lugs	27x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40	Drive Wheel	4,30	
160 A8	4500	40	Free Rolling	4,30	