

TYRES

Product group	Tyres
Item number	15712507
Valid tyre size	385 / 65 - 22.5
LI / SI / PR	155 A8 / 167 A8, 22 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	15712507
EAN	8903094031443
Valid tyre size	385 / 65 - 22.5
Alternative size 1	400/60-22.5
LI / SI / PR	155 A8 / 167 A8, 22 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	60,68
Recommended rim size	AG11.75
Permitted rim size	11.75
Maximum air pressure [bar].	5,90
Section width (mm)	400
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3233
Tread depth (mm)	22,0
Number of lugs	27x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40	Drive Wheel	5,90	
167 A8	5450	40	Free Rolling	5,90	