

TYRES

Product group	Tyres
Item number	15712510
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	136 A8 / 148 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Flotation tyre for high payloads with low inflation pressure
- Minimal soil compaction
- Suitable for road and field use

Technical Informations

Item number	15712510
EAN	8903094006267
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	136 A8 / 148 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,42
Recommended rim size	AG16.00
Maximum air pressure [bar].	2,70
Section width (mm)	500
Outer diameter of tyre [mm].	1045
Stat. radius (SLR) [mm]	471
Rolling circumference [mm].	3167
Tread depth (mm)	19,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40	Drive Wheel	2,70	
148 A8	3150	40	Free Rolling	2,70	