

## TYRES

Product group	Tyres
Item number	15712515
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	142 A8 / 154 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Flotation tyre for high payloads with low inflation pressure
- Minimal soil compaction
- Suitable for road and field use

## Technical Informations

Item number	15712515
EAN	8903094006274
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	142 A8 / 154 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 558
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	60,52
Recommended rim size	AG16.00
Maximum air pressure [bar].	3,60
Section width (mm)	500
Outer diameter of tyre [mm].	1045
Stat. radius (SLR) [mm]	471
Rolling circumference [mm].	3167
Tread depth (mm)	19,0
Number of lugs	26x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40	Drive Wheel	3,60	
154 A8	3750	40	Free Rolling	3,60	