

## TYRES

Product group	Tyres
Item number	15712518
Valid tyre size	500 / 50 - 22.5
LI / SI / PR	146 A8 / 158 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



## Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

## Technical Informations

Item number	15712518
EAN	8903094006335
Valid tyre size	500 / 50 - 22.5
LI / SI / PR	146 A8 / 158 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,36
Recommended rim size	AG16.00
Maximum air pressure [bar].	3,00
Section width (mm)	500
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3200
Tread depth (mm)	22,0
Number of lugs	27x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A8	3000	40	Drive Wheel	3,00	
158 A8	4250	40	Free Rolling	3,00	