

TYRES

Product group	Tyres
Item number	15712526
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	151 A8 / 163 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation V-Line



Notes and features

- Bias flotation tyre for light applications, e.g. on towed and mounted agricultural equipment as well as presses and similar vehicles
- Traction tread pattern for good self-cleaning
- Overlapping lugs in centre area for smooth running characteristics
- Rounded shoulders provide additional protection for green areas and plant stock
- Not suitable for heavy transport vehicles or long road journeys under high load

Technical Informations

Item number	15712526
EAN	8903094006212
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	151 A8 / 163 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation V-Line
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	77,23
Recommended rim size	AG16.00
Permitted rim size	15.00, 17.00
Maximum air pressure [bar].	3,20
Section width (mm)	500
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3489
Tread depth (mm)	26,0
Number of lugs	28x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	4875	40	Drive Wheel	3,20	
163 A8	4875	40	Free Rolling	3,20	