

## TYRES

Product group	Tyres
Item number	15712527
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	145 A8 / 157 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation TR 675



## Notes and features

- The BKT Flotation TR 675 is particularly suitable for soil work and transport jobs
- It can be used on trailers, compact dumpers and working equipment
- The tyre features excellent traction combined with soil conservation

## Technical Informations

Item number	15712527
EAN	8903094019786
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	145 A8 / 157 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation TR 675
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,45
Recommended rim size	AG16.00
Permitted rim size	15.00, 17.00
Maximum air pressure [bar].	2,40
Section width (mm)	500
Outer diameter of tyre [mm].	1181
Stat. radius (SLR) [mm]	534
Rolling circumference [mm].	3505
Tread depth (mm)	38,0
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40	Drive Wheel	2,40	
157 A8	4125	40	Free Rolling	2,40	