

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15712528 |
| Valid tyre size | 500 / 60 - 22.5 |
| LI / SI / PR | 151 A8 / 163 A8, 16 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Flotation TR 675 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Flotation TR 675 is particularly suitable for soil work and transport jobs
- It can be used on trailers, compact dumpers and working equipment
- The tyre features excellent traction combined with soil conservation

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15712528 |
| EAN | 8903094019793 |
| Valid tyre size | 500 / 60 - 22.5 |
| LI / SI / PR | 151 A8 / 163 A8, 16 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Flotation TR 675 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 94,24 |
| Recommended rim size | AG16.00 |
| Permitted rim size | 15.00, 17.00 |
| Maximum air pressure [bar]. | 4,40 |
| Section width (mm) | 500 |
| Outer diameter of tyre [mm]. | 1181 |
| Stat. radius (SLR) [mm] | 534 |
| Rolling circumference [mm]. | 3505 |
| Tread depth (mm) | 38,0 |
| Number of lugs | 17x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 151 A8 | 3450 | 40 | Drive Wheel | 4,40 | |
| 163 A8 | 4875 | 40 | Free Rolling | 4,40 | |