

## TYRES

Product group	Tyres
Item number	15712528
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	151 A8 / 163 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation TR 675



## Notes and features

- The BKT Flotation TR 675 is particularly suitable for soil work and transport jobs
- It can be used on trailers, compact dumpers and working equipment
- The tyre features excellent traction combined with soil conservation

## Technical Informations

Item number	15712528
EAN	8903094019793
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	151 A8 / 163 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation TR 675
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	94,25
Recommended rim size	AG16.00
Permitted rim size	15.00, 17.00
Maximum air pressure [bar].	4,40
Section width (mm)	500
Outer diameter of tyre [mm].	1181
Stat. radius (SLR) [mm]	534
Rolling circumference [mm].	3505
Tread depth (mm)	38,0
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40	Drive Wheel	4,40	
163 A8	4875	40	Free Rolling	4,40	