

TYRES

Product group	Tyres
Item number	15712532
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	154 A8 / 166 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648 T



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	15712532
EAN	8903094029242
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	154 A8 / 166 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648 T
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	77,24
Recommended rim size	AG 16.00
Maximum air pressure [bar].	4,00
Section width (mm)	550
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3203
Tread depth (mm)	22,0
Number of lugs	26x2
Lug width (mm)	41
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40	Drive Wheel	4,00	
166 A8	5300	40	Free Rolling	4,00	