

TYRES

Product group	Tyres
Item number	15712537
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	154 A8 / 166 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 509



Notes and features

- The BKT AS509 was specially developed for agricultural trailers, seeders and soil cultivating machines
- The tyre guarantees high loading capacity with low inflation pressure for minimal soil compaction
- The high number of lugs provides optimal ground pressure distribution

Technical Informations

Item number	15712537
EAN	8903094051038
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	154 A8 / 166 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 509
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	79,70
Recommended rim size	AG16.00
Maximum air pressure [bar].	4,00
Section width (mm)	540
Outer diameter of tyre [mm].	1065
Stat. radius (SLR) [mm]	479
Rolling circumference [mm].	3250
Tread depth (mm)	29,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40	Drive Wheel	4,00	
166 A8	5300	40	Free Rolling	4,00	