

TYRES

Product group	Tyres
Item number	15712546
Valid tyre size	550 / 60 - 22.5
LI / SI / PR	154 A8 / 167 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation V-Line



Notes and features

- Bias flotation tyre for light applications, e.g. on towed and mounted agricultural equipment as well as presses and similar vehicles
- Traction tread pattern for good self-cleaning
- Overlapping lugs in centre area for smooth running characteristics
- Rounded shoulders provide additional protection for green areas and plant stock
- Not suitable for heavy transport vehicles or long road journeys under high load

Technical Informations

Item number	15712546
EAN	8903094006236
Valid tyre size	550 / 60 - 22.5
LI / SI / PR	154 A8 / 167 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation V-Line
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	87,45
Recommended rim size	AG16.00
Maximum air pressure [bar].	2,80
Section width (mm)	550
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3725
Tread depth (mm)	26,0
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40	Drive Wheel	2,80	
167 A8	5450	40	Free Rolling	2,80	