

TYRES

Product group	Tyres
Item number	15712557
Valid tyre size	550 / 60 - 22.5
LI / SI / PR	158 A8 / 171 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	15712557
EAN	8903094038862
Valid tyre size	550 / 60 - 22.5
LI / SI / PR	158 A8 / 171 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	101,69
Recommended rim size	AG16.00
Maximum air pressure [bar].	3,50
Section width (mm)	550
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3725
Tread depth (mm)	26,0
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40	Drive Wheel	3,50	
171 A8	6150	40	Free Rolling	3,50	