

TYRES

Product group	Tyres
Item number	15712572
Valid tyre size	600 / 40 - 22.5
LI / SI / PR	157 A8 / 169 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678



Notes and features

- The TR 678 is suitable for use on excavators and loaders as well as for the agricultural sector with its special, steel belt version.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machinery downtimes and increases efficiency.

Technical Informations

Item number	15712572
EAN	8903094051915
Valid tyre size	600 / 40 - 22.5
LI / SI / PR	157 A8 / 169 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	106,77
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,10
Section width (mm)	615
Outer diameter of tyre [mm].	1085
Stat. radius (SLR) [mm]	483
Rolling circumference [mm].	3264
Tread depth (mm)	38,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40	Drive Wheel	4,10	
169 A8	5800	40	Free Rolling	4,10	