

## TYRES

Product group	Tyres
Item number	15712595
Valid tyre size	600 / 55 - 22.5
LI / SI / PR	156 A8 / 169 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation Rib 774



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT Flotation RIB 774 is the ideal tyre for free rolling agricultural implements and trailers
- Thanks to the fine grooved tread pattern and its flotation characteristics, the soil is optimally protected for the best possible yields
- When used for road transport, the low rolling resistance ensures the lowest possible fuel consumption

## Technical Informations

Item number	15712595
EAN	8903094006632
Valid tyre size	600 / 55 - 22.5
LI / SI / PR	156 A8 / 169 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation Rib 774
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	97,34
Recommended rim size	20.00
Maximum air pressure [bar].	2,60
Section width (mm)	600
Outer diameter of tyre [mm].	1230
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3716
Tread depth (mm)	15,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40	Drive Wheel	2,60	
169 A8	5800	40	Free Rolling	2,60	