

TYRES

Product group	Tyres
Item number	15712597
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	166 B, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678



Notes and features

- The TR 678 is suitable for use on excavators and loaders as well as for the agricultural sector with its special, steel belt version.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machinery downtimes and increases efficiency.

Technical Informations

Item number	15712597
EAN	8903094026517
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	166 B, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	137,35
Recommended rim size	20.0
Maximum air pressure [bar].	4,50
Section width (mm)	650
Outer diameter of tyre [mm].	1150
Stat. radius (SLR) [mm]	502
Rolling circumference [mm].	3302
Tread depth (mm)	38,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 B	5300	50		4,50	