

TYRES

Product group	Tyres
Item number	15712608
Valid tyre size	710 / 40 - 22.5
LI / SI / PR	173 A8
TL/TT	TL
Brand	BKT
Tread pattern	TR 678



Notes and features

- The TR 678 is suitable for use on excavators and loaders as well as for the agricultural sector with its special, steel belt version.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machinery downtimes and increases efficiency.

Technical Informations

Item number	15712608
EAN	8903094064755
Valid tyre size	710 / 40 - 22.5
LI / SI / PR	173 A8
TL/TT	TL
Brand	BKT
Tread pattern	TR 678
TRA Code	LS-2
Carcass properties	HD,Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	158,75
Recommended rim size	AG24.00
Maximum air pressure [bar].	6,00
Section width (mm)	707
Outer diameter of tyre [mm].	1165
Stat. radius (SLR) [mm]	545
Rolling circumference [mm].	3624
Tread depth (mm)	37,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		6,00	