

TYRES

Product group	Tyres	
Item number	15712830	
Valid tyre size	600 / 55 - 26.5	
LI / SI / PR	172 A2 / 165 A8, 20 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	Forestech	





Notes and features

- Suitable for timber harvesting machines and tow tractors
- Rugged casing guarantees high load capacity
- Reinforced bead and lug area for a long service life



Technical Informations

Item number	15712830
EAN	8903094031238
Valid tyre size	600 / 55 - 26.5
LI / SI / PR	172 A2 / 165 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Forestech
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	193,21
Recommended rim size	20.00
Maximum air pressure [bar].	5,00
Section width (mm)	610
Outer diameter of tyre [mm].	1335
Stat. radius (SLR) [mm]	618
Rolling circumference [mm].	4032
Tread depth (mm)	32,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		5,00	
165 A8	5150	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.