Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres
Item number	15712845
Valid tyre size	520 / 50 - 17
LI / SI / PR	147 B / 159 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Flotation 647





Notes and features

- The BKT Flotation 647 is a bias tyre for agricultural vehicles used on soft soil and grasslands
- Due to the wide contact area and the special tread pattern, the pressure on the ground is optimally distributed and the soil is protected
- The flotation tread pattern provides very good selfcleaning properties

Bohnenkamp Moving Professionals

Technical Informations

item number15712845EAN90309403314Valid tyre size520/50-17L/ JSI / PR478 / JS9 BTuTTTuBrandBKTFread patternFolaion 647AristaticNoEC regulation numberEC 106Recommender finisceAide 000Anistani (La guardianti and transmitter)Aide 000BrandSch 000BrandBis ACommender finisceAide 000AnistationAide 000Brandmain finisceAide 000Brandmain finisceAide 000Brandmain finisceSch 000Bra		
Valid tyre sizeS20/50-17LI / SI / PR147 B / 159 BT.J.TT147 B / 159 BBrandBKTFred patternFlotation 647AntistaticNoTyre colourBlackECE regulation numberSci 106Metogewicht [kg] (gültig)Sci 4.4Anisman air pressure [bar]100Stat. radius (SLR) [mm]195Stat. radius (SLR) [mm]195Tead depth (nm)195Mater of Lug195Tead depth (nm)195Mater of Lug195Tead depth (nm)195Mater of Lug195Mater of Lug195Tead depth (nm)195Mater of Lug195Mater of Lug196Mater of Lug196	Item number	15712845
Li / Si / PR147 B / 159 BLi / Si / PR147 B / 159 BTurnITuIBandBKTTread patternFlotation 647AnistaticNoDiackEcc 106Ecc regulation numberSc.4 4Actogewicht [kg] (gilt)g)Sc.44Anistani pressure [backAdio.0Station width (mm)Si6DiackSc.9Ausinum air pressure [back]Si6Ausinum air pressure [back]Si6Diack for [back]Si6Curre diameter of tyre [mm]Si6Ausinum for sure [back]Si6Ausinum for s	EAN	8903094063314
TLTII.TLTTII.BrandIKTBrandIKTTread patternFloation 647AristaticNoTyre colourBlackTet regulation numberICE 106Becomended rim sizeAdi6.00Ausimum air pressure [lata]OloSection vidth (moj)ISGOtar dianeer of tyre [moj)ISGBelling circums[remotion]ISGTead depth (moj)ISGAusimum air pressure [lata]ISGSection vidth (moj)ISGIst radius (SLR) [moj)ISGIst radius (SLR) [moj)ISGAusimum air pressure [lata]ISGSection vidth (moj)ISGIst radius (SLR) [moj)ISGIst radius (SLR) [moj)IS	Valid tyre size	520 / 50 - 17
BrandBKTFread patternFotation 647AnistaticNoTyre colourBlackECE regulation numberECE 106Stotogewicht [tgt] (gültig)5.6.4Actogewicht [sd] (gültig)1.6.0Maximum air pressure [bar]1.6.0Section width (mm)1.6Bata data (SLR) [mm]2.9.7Rading structure [mm]1.9.7Fread enter (mm)1.9.7Bata data (SLR) [mm]2.9.7Tread enter (mm)1.9.2Bata data (SLR) [mm]2.9.7Bata (SLR) [mm]	LI / SI / PR	147 B / 159 B
Tread patternFlotation 647Tread patternFlotation 647AntistaticNoTyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (gültig)56,44Actonomended rim sizeAG16.00Maximum air pressure [bas]100Section width (mm)105Section size [stat. radius (SLR) [mm]2097Tread depth (mm)10,5Tread depth (mm)10,5Mumber of Ligs20,2	TL/TT	TL
AnistaticNoAnistaticNoTyre colourBlackBackBlackECE regulation numberCE 106Actogewicht [kg] (giltig)Sol.44Recommended rins sizeAG1.00Maximun air pressure [bar]JoSettion width (mm)SolSettion sizeSolAuter diameter of tyre [mm]SolTrad leght (mm)SolJuber of LugsSolAuter of LugsSolSettion width (mm)SolSettion width (mm)Sol<	Brand	ВКТ
Tyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (ültig)56.44Recommended rim sizeAG16.00Maximun air pressure [bar]4.00Section width (mm)516Outer diameter of tyre [mm]959Stat. radius (SLR) [mm]2907Tread depth (mm)9.10Jumber of Lugs24.2	Tread pattern	Flotation 647
ECE regulation numberECE 106Nettogewicht [kg] (gültig)56,44Recommended rim sizeAG16.00Maximum air pressure [ba]4,00Section width (mm)516Otter diameter of tyre [mm]965Stat. radius (SLR) [mm]2907Tread depth (mm)19,5Number of lugs442	Antistatic	No
Nettogewicht [kg] (gültig)56,44Recommended rim sizeAG16.00Maximum air pressure [bai]4,00Section width (mm)516Otter diameter of tyre [mm]965Stat. radius (SLR) [mm]426Rolling circumference [mm]19,07Tread depth (mm)19,5Jumber of lugs24×2	Tyre colour	Black
Recommended rim sizeAG16.00Maximum air pressure [ba]4,00Section width (mm)516Outer diameter of tyre [m]965Stat. radius (SLR) [mm]240Rolling circumference [mm]19,5Number of lugs242	ECE regulation number	ECE 106
Maximum air pressure [bar]4,00Section width (mm)516Outer diameter of tyre [mm]965Stat. radius (SLR) [mm]420Rolling circumference [mm]19,5Number of lugs242	Nettogewicht [kg] (gültig)	56,44
Section width (mm)516Outer diameter of tyre [mm]965Stat. radius (SLR) [mm]426Rolling circumference [mm]907Tread depth (mm)19,5Number of lugs242	Recommended rim size	AG16.00
Outer diameter of tyre [mm]965Stat. radius (SLR) [mm]426Rolling circumference [mm]2907Tread depth (mm)19,5Number of lugs2422	Maximum air pressure [bar].	4,00
Stat. radius (SLR) [mm] 426 Rolling circumference [mm] 2907 Tread depth (mm) 19,5 Number of lugs 2422	Section width (mm)	516
Rolling circumference [mm] 2907 Tread depth (mm) 19,5 Number of lugs 24x2	Outer diameter of tyre [mm].	965
Tread depth (mm) 19,5 Number of lugs 24x2	Stat. radius (SLR) [mm]	426
Number of lugs 24x2	Rolling circumference [mm].	2907
	Tread depth (mm)	19,5
E-Ready No	Number of lugs	24x2
	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 B	3075	50	Drive Wheel	4,00	
159 B	4375	50	Free Rolling	4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.