

## TYRES

Product group	Tyres
Item number	15712855
Valid tyre size	700 / 50 - 26.5
LI / SI / PR	162 A8 / 174 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



## Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

## Technical Informations

Item number	15712855
EAN	8903094006526
Valid tyre size	700 / 50 - 26.5
LI / SI / PR	162 A8 / 174 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	136,20
Recommended rim size	24.00
Permitted rim size	AG 24.00
Maximum air pressure [bar].	2,40
Section width (mm)	700
Outer diameter of tyre [mm].	1354
Stat. radius (SLR) [mm]	581
Speed Radius Index (SRI)	575
Rolling circumference [mm].	4017
Tread depth (mm)	26,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40	Drive Wheel	2,40	
174 A8	6700	40	Free Rolling	2,40	