

## **TYRES**

Product group	Tyres	
Item number	15712860	
Valid tyre size	710 / 45 - 26.5	
LI / SI / PR	175 A2 / 168 A8, 20 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	Forestech	





## **Notes and features**

- Suitable for timber harvesting machines and tow tractors
- Rugged casing guarantees high load capacity
- Reinforced bead and lug area for a long service life



## **Technical Informations**

Item number	15712860
EAN	8903094029754
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Forestech
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	225,24
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	620
Rolling circumference [mm].	4047
Tread depth (mm)	32,0
Number of lugs	18x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		5,00	
168 A8	5600	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.