

## TYRES

|                 |                        |
|-----------------|------------------------|
| Product group   | Tyres                  |
| Item number     | 15712860               |
| Valid tyre size | 710 / 45 - 26.5        |
| LI / SI / PR    | 175 A2 / 168 A8, 20 PR |
| TL/TT           | TL                     |
| Brand           | BKT                    |
| Tread pattern   | Forestech              |



## Notes and features

- Suitable for timber harvesting machines and tow tractors
- Rugged casing guarantees high load capacity
- Reinforced bead and lug area for a long service life

## Technical Informations

|                              |                        |
|------------------------------|------------------------|
| Item number                  | 15712860               |
| EAN                          | 8903094029754          |
| Valid tyre size              | 710 / 45 - 26.5        |
| LI / SI / PR                 | 175 A2 / 168 A8, 20 PR |
| TL/TT                        | TL                     |
| Brand                        | BKT                    |
| Tread pattern                | Forestech              |
| TRA Code                     | LS-2                   |
| Antistatic                   | No                     |
| Tyre colour                  | Black                  |
| ECE regulation number        | ECE 106                |
| Nettogewicht [kg] (gültig)   | 225,24                 |
| Recommended rim size         | 24.00                  |
| Maximum air pressure [bar].  | 5,00                   |
| Section width (mm)           | 710                    |
| Outer diameter of tyre [mm]. | 1340                   |
| Stat. radius (SLR) [mm]      | 620                    |
| Rolling circumference [mm].  | 4047                   |
| Tread depth (mm)             | 32,0                   |
| Number of lugs               | 18x2                   |
| E-Ready                      | No                     |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 175 A2 | 6900               | 10           |               | 5,00                     |              |
| 168 A8 | 5600               | 40           |               | 5,00                     |              |