

TYRES

Product group	Tyres	
Item number	15712890	
Valid tyre size	750 / 55 - 26.5	
LI / SI / PR	184 A2 / 177 A8, 20 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Forestech	





Notes and features

- Suitable for timber harvesting machines and tow tractors
- Rugged casing guarantees high load capacity
- Reinforced bead and lug area for a long service life



Technical Informations

Item number	15712890
EAN	8903094031719
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	184 A2 / 177 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Forestech
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	280,40
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	5,00
Section width (mm)	755
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	680
Rolling circumference [mm].	4467
Tread depth (mm)	32,0
Number of lugs	19x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A2	9000	10		5,00	
177 A8	7300	40		5,00	