

## TYRES

Product group	Tyres
Item number	15712910
Valid tyre size	650 / 65 - 30.5
LI / SI / PR	167 A8 / 179 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



## Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

## Technical Informations

Item number	15712910
EAN	8903094006465
Valid tyre size	650 / 65 - 30.5
LI / SI / PR	167 A8 / 179 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	190,05
Recommended rim size	AG20.00
Maximum air pressure [bar].	2,20
Section width (mm)	650
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	710
Rolling circumference [mm].	4935
Tread depth (mm)	26,0
Number of lugs	40x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40	Drive Wheel	2,20	
179 A8	7750	40	Free Rolling	2,20	