

TYRES

Product group	Tyres
Item number	15715080
Valid tyre size	VF 400 / 45 R 17.5
LI / SI / PR	159 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

Technical Informations

Item number	15715080
EAN	8903094063598
Valid tyre size	VF 400 / 45 R 17.5
LI / SI / PR	159 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,53
Recommended rim size	14.00
Maximum air pressure [bar].	6,00
Section width (mm)	400
Outer diameter of tyre [mm].	800
Stat. radius (SLR) [mm]	343
Speed Radius Index (SRI)	390
Rolling circumference [mm].	2357
Tread depth (mm)	11,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		6,00	