

TYRES

Product group	Tyres
Item number	15715090
Valid tyre size	VF 445 / 65 R 22.5
LI / SI / PR	169 D
TL/TT	TL
Brand	BKT
Tread pattern	SR 713



Notes and features

- The BKT SR 713 is an all-steel radial tyre for use on agricultural equipment.
- Compared to the standard tyre, the tyre offers up to 40% higher load capacity at the same inflation pressure, or the same load capacity at an inflation pressure reduced by up to 40% due to its VF technology.
- The strong casing with multi-layered steel bands ensures a long service life.
- The multi-groove tread pattern and its large contact area reduce soil compaction and enable slow and even wear.
- On the road, the tyre is characterised by reliability and speeds of up to 65 km/h.

Technical Informations

Item number	15715090
EAN	8903094059416
Valid tyre size	VF 445 / 65 R 22.5
LI / SI / PR	169 D
TL/TT	TL
Brand	BKT
Tread pattern	SR 713
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	101,34
Recommended rim size	13.00
Permitted rim size	14.00
Maximum air pressure [bar].	4,40
Section width (mm)	440
Outer diameter of tyre [mm].	1160
Stat. radius (SLR) [mm]	533
Rolling circumference [mm].	3515
Tread depth (mm)	19,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		4,40	