

TYRES

Product group	Tyres
Item number	15715106
Valid tyre size	500 / 60 R 22.5
LI / SI / PR	166 A8 / 155 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Ultra



Notes and features

- The BKT FL630 Ultra is a flotation tyre for use in the field and on the road
- It is mostly suitable for agricultural trailers, balers, heavy seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction and optimum soil protection
- When driving on the road, the tyre is characterised by high ride comfort and low noise emission

Technical Informations

Item number	15715106
EAN	8903094046065
Valid tyre size	500 / 60 R 22.5
LI / SI / PR	166 A8 / 155 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Ultra
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	98,60
Recommended rim size	AG16.00
Permitted rim size	15.00, 17.00
Maximum air pressure [bar].	4,00
Section width (mm)	503
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	521
Rolling circumference [mm].	3592
Tread depth (mm)	29,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		4,00	
155 D	3875	65		4,00	