

## TYRES

|                 |                  |
|-----------------|------------------|
| Product group   | Tyres            |
| Item number     | 15715116         |
| Valid tyre size | 560 / 45 R 22.5  |
| LI / SI / PR    | 152 D            |
| TL/TT           | TL               |
| Brand           | BKT              |
| Tread pattern   | Ridemax FL 693 M |



## Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

## Technical Informations

|                              |                  |
|------------------------------|------------------|
| Item number                  | 15715116         |
| EAN                          | 8903094037322    |
| Valid tyre size              | 560 / 45 R 22.5  |
| LI / SI / PR                 | 152 D            |
| TL/TT                        | TL               |
| Brand                        | BKT              |
| Tread pattern                | Ridemax FL 693 M |
| Carcass properties           | Steel Belted     |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | ECE 106          |
| Nettogewicht [kg] (gültig)   | 98,90            |
| Recommended rim size         | AG16.00          |
| Maximum air pressure [bar].  | 4,00             |
| Section width (mm)           | 543              |
| Outer diameter of tyre [mm]. | 1076             |
| Stat. radius (SLR) [mm]      | 457              |
| Rolling circumference [mm].  | 3306             |
| Tread depth (mm)             | 21,0             |
| Tyre capacity 75% [ltr.]     | 185              |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 152 D | 3550               | 65           |               | 4,00                     |              |
| 0     |                    |              |               | 4,00                     |              |