

TYRES

Product group	Tyres
Item number	15715118
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	163 A8 / 152 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639



Notes and features

- Traction tyre for mixed road and field use with high load volume
- Good self-cleaning and overlapping centre lugs for good ride comfort
- High load capacity, even with low inflation pressure, in combination with a wide contact area for optimal ground protection

Technical Informations

Item number	15715118
EAN	8903094034260
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	163 A8 / 152 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	96,50
Recommended rim size	AG16.00
Maximum air pressure [bar].	4,00
Section width (mm)	543
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	484
Rolling circumference [mm].	3303
Tread depth (mm)	29,0
Tyre capacity 75% [ltr.]	180
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A8	4875	40		4,00	
152 D	3550	65		4,00	