

TYRES

Product group	Tyres
Item number	15715129
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	170 A8 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639



Notes and features

- Traction tyre for mixed road and field use with high load volume
- Good self-cleaning and overlapping centre lugs for good ride comfort
- High load capacity, even with low inflation pressure, in combination with a wide contact area for optimal ground protection

Technical Informations

Item number	15715129
EAN	8903094028153
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	170 A8 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	109,50
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	611
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	521
Rolling circumference [mm].	3592
Tread depth (mm)	31,0
Tyre capacity 75% [ltr.]	251
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A8	6000	40		4,00	
159 D	4375	65		4,00	