

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15715137 |
| Valid tyre size | 580 / 65 R 22.5 |
| LI / SI / PR | 166 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 630 Super |



Notes and features

- Flotation tyre with steel belt reinforcement for use on slurry tankers, manure spreaders and similar towed agricultural vehicles
- Optimised tread pattern, larger contact area between lugs and ground for smoother driving
- Designed more for use in fields and on arable land
- Extreme puncture resistance

Technical Informations

| | |
|------------------------------|---------------------------|
| Item number | 15715137 |
| EAN | 8903094045037 |
| Valid tyre size | 580 / 65 R 22.5 |
| LI / SI / PR | 166 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 630 Super |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 125,92 |
| Recommended rim size | AG18.00 |
| Permitted rim size | AG16.00, AG17.00, AG20.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 577 |
| Outer diameter of tyre [mm]. | 1326 |
| Stat. radius (SLR) [mm] | 594 |
| Rolling circumference [mm]. | 4058 |
| Tread depth (mm) | 24,5 |
| Number of lugs | 23x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 166 D | 5300 | 65 | | 4,00 | |