

TYRES

Product group	Tyres	
Item number	15715138	
Valid tyre size	620 / 40 R 22.5	
LI / SI / PR	154 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	FL 635	





Notes and features

- Modern flotation tyre with traction block tread
- Robust heavy-duty nylon casing with strengthened polyester belt plies
- Particularly suitable for balers (especially for green fodder recovery) and other towed agricultural machines
- Open block tread pattern and rounded shoulders ensure optimal grassland protection
- Traction tread pattern ensures good grip in wet conditions as well as fast self-cleaning



Technical Informations

Item number	15715138
EAN	8903094048038
Valid tyre size	620 / 40 R 22.5
LI / SI / PR	154 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	102.42
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	625
Outer diameter of tyre [mm].	1068
Stat. radius (SLR) [mm]	470
Rolling circumference [mm].	3249
Tread depth (mm)	28,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.