

## TYRES

Product group	Tyres
Item number	15715139
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	172 A8 / 161 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Ultra



## Notes and features

- The BKT FL630 Ultra is a flotation tyre for use in the field and on the road
- It is mostly suitable for agricultural trailers, balers, heavy seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction and optimum soil protection
- When driving on the road, the tyre is characterised by high ride comfort and low noise emission

## Technical Informations

Item number	15715139
EAN	8903094052509
Valid tyre size	560 / 60 R 22.5
Alternative size 1	550/60R22.5
LI / SI / PR	172 A8 / 161 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Ultra
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	112,50
Recommended rim size	AG16.00
Permitted rim size	16.00, 17.00, AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	543
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	535
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3760
Tread depth (mm)	28,5
Number of lugs	20x2
Tyre capacity 75% [litr.]	374
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		4,00	
161 D	4625	65		4,00	