

TYRES

Product group	Tyres	
Item number	15715140	
Valid tyre size	710 / 40 R 22.5	
LI / SI / PR	172 A8 / 161 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	FL 639	





Notes and features

- Traction tyre for mixed road and field use with high load volume
- Good self-cleaning and overlapping centre lugs for good ride comfort
- High load capacity, even with low inflation pressure, in combination with a wide contact area for optimal ground protection



Technical Informations

Item number	15715140
EAN	8903094041176
Valid tyre size	710 / 40 R 22.5
LI / SI / PR	172 A8 / 161 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	124,66
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	727
Outer diameter of tyre [mm].	1140
Stat. radius (SLR) [mm]	503
Rolling circumference [mm].	3492
Tread depth (mm)	30,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		4,00	
161 D	4625	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.