

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15715145 |
| Valid tyre size | 600 / 55 R 22.5 |
| LI / SI / PR | 162 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 630 Super |



Notes and features

- Flotation tyre with steel belt reinforcement for use on slurry tankers, manure spreaders and similar towed agricultural vehicles
- Optimised tread pattern, larger contact area between lugs and ground for smoother driving
- Designed more for use in fields and on arable land
- Extreme puncture resistance

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15715145 |
| EAN | 8903094056149 |
| Valid tyre size | 600 / 55 R 22.5 |
| LI / SI / PR | 162 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 630 Super |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 122,46 |
| Recommended rim size | AG20.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 595 |
| Outer diameter of tyre [mm]. | 1232 |
| Stat. radius (SLR) [mm] | 560 |
| Speed Radius Index (SRI) | 575 |
| Rolling circumference [mm]. | 3757 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 162 D | 4750 | 65 | | 4,00 | |