

TYRES

Product group	Tyres
Item number	15715146
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Super



Notes and features

- Flotation tyre with steel belt reinforcement for use on slurry tankers, manure spreaders and similar towed agricultural vehicles
- Optimised tread pattern, larger contact area between lugs and ground for smoother driving
- Designed more for use in fields and on arable land
- Extreme puncture resistance

Technical Informations

Item number	15715146
EAN	8903094060900
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Super
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	116,12
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	611
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	518
Rolling circumference [mm].	3533
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		4,00	