

TYRES

Product group	Tyres
Item number	15715150
Valid tyre size	650 / 55 R 22.5
LI / SI / PR	167 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635





Notes and features

- Modern flotation tyre with traction block tread
- Robust heavy-duty nylon casing with strengthened polyester belt plies
- Particularly suitable for balers (especially for green fodder recovery) and other towed agricultural machines
- Open block tread pattern and rounded shoulders ensure optimal grassland protection
- Traction tread pattern ensures good grip in wet conditions as well as fast self-cleaning



Technical Informations

Item number	15715150
EAN	8903094043521
Valid tyre size	650 / 55 R 22.5
LI / SI / PR	167 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	131,53
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	645
Outer diameter of tyre [mm].	1287
Stat. radius (SLR) [mm]	568
Rolling circumference [mm].	3901
Tread depth (mm)	29,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.