

TYRES

Product group	Tyres
Item number	15715166
Valid tyre size	710 / 35 R 22.5
LI / SI / PR	157 D / 154 E
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

Technical Informations

Item number	15715166
EAN	8903094056132
Valid tyre size	710 / 35 R 22.5
LI / SI / PR	157 D / 154 E
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	113,95
Recommended rim size	AG 24.00
Maximum air pressure [bar].	4,00
Section width (mm)	712
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	482
Rolling circumference [mm].	3254
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 D	4125	65		4,00	
154 E	3750	70		4,00	