

TYRES

Product group	Tyres
Item number	15715168
Valid tyre size	710 / 40 R 22.5
LI / SI / PR	161 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635



Notes and features

- Modern flotation tyre with traction block tread
- Robust heavy-duty nylon casing with strengthened polyester belt plies
- Particularly suitable for balers (especially for green fodder recovery) and other towed agricultural machines
- Open block tread pattern and rounded shoulders ensure optimal grassland protection
- Traction tread pattern ensures good grip in wet conditions as well as fast self-cleaning

Technical Informations

Item number	15715168
EAN	8903094053285
Valid tyre size	710 / 40 R 22.5
LI / SI / PR	161 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	124,30
Recommended rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	727
Outer diameter of tyre [mm].	1140
Stat. radius (SLR) [mm]	510
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3467
Tread depth (mm)	24,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 D	4625	65		4,00	