Bohnenkamp Moving Professionals

17.11.2024

TYRES

Product group	Tyres
Item number	15715170
Valid tyre size	750 / 45 R 22.5
LI / SI / PR	168 D
TL/TT	TL
Brand	ВКТ
Tread pattern	FL 635





Notes and features

- Modern flotation tyre with traction block tread
- Robust heavy-duty nylon casing with strengthened polyester belt plies
- Particularly suitable for balers (especially for green fodder . recovery) and other towed agricultural machines
- Open block tread pattern and rounded shoulders ensure • optimal grassland protection
- Traction tread pattern ensures good grip in wet conditions • as well as fast self-cleaning

Bohnenkamp Moving Professionals

Technical Informations

Item number	15715170
EAN	8903094048786
Valid tyre size	750 / 45 R 22.5
LI / SI / PR	168 D
TL/TT	TL
Brand	ВКТ
Tread pattern	FL 635
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	143,53
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	754
Outer diameter of tyre [mm].	1247
Stat. radius (SLR) [mm]	555
Rolling circumference [mm].	3810
Tread depth (mm)	30,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.