

TYRES

Product group	Tyres
Item number	15715180
Valid tyre size	28L R 26
LI / SI / PR	176 A8 / 173 B
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 690



Notes and features

- Suitable for manure spreaders, transfer vehicles and other towed agricultural vehicles with approx. 75 % road use.
- Tread pattern design with low rolling resistance for low fuel consumption.
- Rugged casing with steel belt reinforcement provides additional load capacity and protection against punctures.

Technical Informations

Item number	15715180
EAN	8903094034321
Valid tyre size	28L R 26
Alternative size 1	750/65R26
LI / SI / PR	176 A8 / 173 B
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 690
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	230,37
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	2,80
Section width (mm)	719
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	695
Rolling circumference [mm].	4745
Tread depth (mm)	30,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,80	
173 B	6500	50		2,80	