Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15715221	
Valid tyre size	710 / 50 R 26.5	
LI / SI / PR	181 A8 / 170 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	FL 630 Ultra	



Notes and features

- The BKT FL630 Ultra is a flotation tyre for use in the field • and on the road
- It is mostly suitable for agricultural trailers, balers, heavy ٠ seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces • and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction • and optimum soil protection
- When driving on the road, the tyre is characterised by • high ride comfort and low noise emission

Bohnenkamp Moving Professionals

Technical Informations

Item number	15715221
EAN	8903094047284
Valid tyre size	710 / 50 R 26.5
LI / SI / PR	181 A8 / 170 D
TL/TT	TL
Brand	ВКТ
Tread pattern	FL 630 Ultra
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	164,51
Recommended rim size	AG24.00
Permitted rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	727
Outer diameter of tyre [mm].	1383
Stat. radius (SLR) [mm]	599
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4208
Tread depth (mm)	30,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		4,00	
170 D	6000	65		4,00	

13.03.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.