

## TYRES

Product group	Tyres
Item number	15715222
Valid tyre size	650 / 55 R 26.5
LI / SI / PR	178 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



## Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

## Technical Informations

Item number	15715222
EAN	8903094049622
Valid tyre size	650 / 55 R 26.5
LI / SI / PR	178 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Carcass properties	HD,Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	161,60
Recommended rim size	AG 20.00
Maximum air pressure [bar].	6,00
Section width (mm)	645
Outer diameter of tyre [mm].	1389
Stat. radius (SLR) [mm]	609
Rolling circumference [mm].	4250
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 D	7500	65		6,00	