

TYRES

Product group	Tyres	
Item number	15715224	
Valid tyre size	650 / 55 R 26.5	
LI / SI / PR	178 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	FL 695	





Notes and features

- The BKT FL 695 is a flotation radial tyre for trailers in construction and transport use.
- The special tread pattern with tread blocks arranged in the centre of the tread guarantees very good selfcleaning.
- The strong carcass allows for excellent stability and high load capacities under all ground conditions.
- Steel inserts protect the tyre from damage.



Technical Informations

Item number	15715224
EAN	8903094067886
Valid tyre size	650 / 55 R 26.5
LI / SI / PR	178 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 695
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	207,09
Recommended rim size	AG20.00
Permitted rim size	AG22.00
Maximum air pressure [bar].	6,00
Section width (mm)	630
Outer diameter of tyre [mm].	1390
Stat. radius (SLR) [mm]	630
Rolling circumference [mm].	4242
Tread depth (mm)	26,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 D	7500	65		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.