

TYRES

Product group	Tyres
Item number	15715228
Valid tyre size	850 / 40 R 26.5
LI / SI / PR	184 A8 / 173 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639



Notes and features

- Traction tyre for mixed road and field use with high load volume
- Good self-cleaning and overlapping centre lugs for good ride comfort
- High load capacity, even with low inflation pressure, in combination with a wide contact area for optimal ground protection

Technical Informations

Item number	15715228
EAN	8903094064779
Valid tyre size	850 / 40 R 26.5
LI / SI / PR	184 A8 / 173 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 639
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	195,30
Recommended rim size	AG28.00
Maximum air pressure [bar].	4,00
Section width (mm)	860
Outer diameter of tyre [mm].	1355
Stat. radius (SLR) [mm]	599
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4122
Tread depth (mm)	31,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		4,00	
173 D	6500	65		4,00	