

## **TYRES**

Product group	Tyres	
Item number	15715231	
Valid tyre size	800 / 45 R 26.5	
LI / SI / PR	184 A8 / 174 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	FL 630 Ultra	





## Notes and features

- The BKT FL630 Ultra is a flotation tyre for use in the field and on the road
- It is mostly suitable for agricultural trailers, balers, heavy seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction and optimum soil protection
- When driving on the road, the tyre is characterised by high ride comfort and low noise emission



## **Technical Informations**

Item number	15715231
EAN	8903094054831
Valid tyre size	800 / 45 R 26.5
LI / SI / PR	184 A8 / 174 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 630 Ultra
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	187,30
Recommended rim size	AG28.00
Permitted rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	828
Outer diameter of tyre [mm].	1393
Stat. radius (SLR) [mm]	618
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4238
Tread depth (mm)	31,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		4,00	
174 D	6700	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.